


We always make Tapes !



Synthetic Rubber

Packaging tape with natural rubber, one-sidedly glueing, made on a strong and resistant PP foil. These tapes are perfect for sealing light and heavy cartons.

The tapes are available in colors: white, brown, transparent.

Standard size:

- ✓ Width– 19mm, 25mm, 30mm, 38mm, 45mm, 48mm, 50mm, 72mm, 75mm
- ✓ Lenght – 54m, 60m, 66m, 900m, 990m



Technical data:

Fomite Foil BOPP	Hot Melt	Super Hot Melt	Freezer
Adhesiveness (ball method)	7 cm	5 cm	6 cm
Grip with steel (for 180 angle)	12,5 N/cal	15,5 N/cal	13,5 N/cal
Elongation during rupture (flexibility)	160 %	160 %	160 %
Foil thickness	25 µm	28 µm	25 µm
Overall thickness	45 µm	50 µm	45 µm
Adhesive amount	17 g/m ²	20 g/m ²	17 g/m ²
Adhesive type	Syntethetic rubber	Syntethetic rubber	Syntethetic rubber
Temperaturr during application	6°C to 45°C	6°C to 45°C	6°C to 45°C
Temperature endurance after application	-10°C to 60°C	-10°C to 60°C	-21°C to 45°C

Measurement latitude +/- 3%*

There is a possibility of product change on customer's demand.

Information above represents average data obtained during tests and analysis, conducted under the norms, on randomly selected production samples, and they are not a warranty for official usage. Because many conditions can affect technical parameters of products, we suggest that the user, before making the final decision, verified it himself if the given article meets his requirements and technical aspects.

Storage

Guaranteed capability of the tape in the first 12 months. Tape rolls have to be protected from long-term sunlight activity and other sources of UV. Advised storage temperature spectrum is: 10°C to 25°C. Advised storage moisture spectrum is: 20% to 80%.

Safety

The product does not contain any dangerous or unhealthy ingredients. All of our tapes are compliant with European directive of packagings 2004/12/C.